

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 12420-3 (1988): Circular Audio Connectors, Part 3: Plug, Five Contacts, Nonrigid Type 12420 IS-02 [LITD 3: Electromechanical Components and Mechanical Structures for Electronic Equipment]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard

SPECIFICATION FOR
CIRCULAR AUDIO CONNECTORS


PART 3 PLUG, FIVE CONTACTS, NONRIGID TYPE 12420 IS-02

0. General — This standard shall be read in conjunction with IS : 12420 (Part 1) 'Specification for circular audio connectors: Part 1 Test schedule and requirements'.

1. Type Designation — The type designation [see 4.1 of IS : 12420 (Part 1)], type of contact and typical mating connector for this type of connector are given below:

Type No,	Type of Contact	Typical Mating Connector
12420 IS-02	Solder	12420 IS-03

2. Outline and Dimensions — The outline and dimensions shall be according to Fig. 1.



All dimensions in millimetres.

FIG. 1 OUTLINE AND DIMENSIONS

3. Material, Finish and Life — The material, finish and life requirement shall be as given below:

a) *Material*

Outer shell : Diecast alloy
Dielectric : DAP/Rubber
Contact : Be-Cu gold plated
Mounting parts : Brass

b) *Finish*

All shell and mounting parts to be finished to cadmium plate with olive drab chromatic finish.

c) *Mechanical* : 1 500 mating cycles at a rate of 30 cycles/minute.

4. Climatic Category

a) Temperature severity : -55 to $+85$ °C
b) Damp heat severity : 56 days
c) Air pressure severity : 8.5 kPa
d) Acceleration (Steady state) : 170 m/s^2
e) Vibration : 10 to 55 Hz
f) Shock : 500 m/s^2

5. Electrical Characteristics

a) Current rating : 500 mA, Max
b) Voltage rating : 60 V, Max
c) Contact resistance : 40 milliohms

Adopted 24 June 1988

© November 1988, BIS

Gr 1

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

IS : 12420 (Part 3) - 1988

6. Tests — *See 8* of IS : 12420 (Part 1).

7. Marking — *See 5* of IS : 12420 (Part 1).

EXPLANATORY NOTE

This standard is based on JSS 50 831 (Nov 1972) 'Detail specification for connectors, circular, audio'. The types of connectors covered in this standard are equivalent to pattern JSS 50 831/02-01.